

JBS&G (68409 – 169,482)

AMR005 Airborne Asbestos Fibre Monitoring Report, Finucane Reserve (Rev 0)

24 July 2025

Noah Walsh-Gay
Randwick City Council
Via email: noah.walsh-gay@randwick.nsw.gov.au

**AMR005: Airborne Asbestos Fibre Monitoring Report
Finucan Reserve, 1 Finucane Crescent Matraville, NSW**

Dear Noah,

Please find as **Attachment 1**, the airborne asbestos fibre monitoring results for works associated with Finucane Reserve, located at 1 Finucane Crescent, Matraville NSW (the site) on **Wednesday 23 July 2025**.


All air monitoring was completed in accordance with the *Guidance Note on the Membrane Filter Method for Estimating Airborne Asbestos Fibres* [NOHSC: 3003(2005)], with NATA certification applying to all sample collection, handling, and analytical procedures.

All reported results were satisfactory and conform with the minimum action level of 0.01 fibres /mL for control monitoring as outlined in:

- Work, Health and Safety (2017) Regulation; and
- Safework NSW (2022) Code of Practice – *How to Safely Remove Asbestos*.

If you have any questions regarding these results, please feel free to contact the undersigned on 02 8245 0300 or by email mnoujaim@jbsg.com.au.

Yours sincerely:



Milad Noujaim
Environmental Consultant
SafeWork NSW Licensed Asbestos Assessor (LAA 002002)
JBS&G Australia Pty Ltd

1 Asbestos Air Monitoring Results

JBS & G Australia (NSW) P/L
Level 8, 179 Elizabeth St
Sydney
NSW 2000



NATA Accredited
Accreditation Number 1261
Site Number 18217

Accredited for compliance with ISO/IEC 17025–Testing
 NATA is a signatory to the ILAC Mutual Recognition
 Arrangement for the mutual recognition of the
 equivalence of testing, medical testing, calibration,
 inspection, proficiency testing scheme providers and
 reference materials producers reports and certificates.

Attention: Milad Noujaim
Report 1247772-AFC
Project Name FINUCANE CRES DSI
Project ID 68409
Received Date Jul 23, 2025
Date Reported Jul 23, 2025

METHODOLOGY:

Asbestos Sampling	Sampling as per the National Occupational Health & Safety Commission – Guidance Note on The Membrane Filter Method For Estimating Airborne Asbestos Fibres 2nd Edition [NOHSC:3003(2005)] and the NATA Specific Accreditation Criteria, ISO/IEC 17025 Application Document Life Sciences – Annex, Asbestos sampling and testing, Issued: April 2025.
Pump Calibration	Air sampling pump performance has been assessed in accordance with Australian Institute of Occupational Hygiene (AIOH) Technical Paper Air Sampling Pumps: Equipment Calibration Requirements. Pump flow rate measurement equipment (e.g. Field Rotameter) has been calibrated in accordance with AIOH Technical Paper Flow Measurement Equipment: Calibration Requirements.
Asbestos Counting	Fibre counting is conducted in accordance with the National Occupational Health & Safety Commission Guidance Note on the Membrane Filter Method For Estimating Airborne Asbestos Fibres 2nd Edition , [NOHSC:3003(2005)] (MFM) and supplementary work instruction in-house LTM-ASB-8010. Unless specifically noted, analysis is undertaken by approved analysts at the base facility. Fibre counts (Fibres/fields) are covered by the facility's NATA scope of accreditation. The requirements of the NATA Specific Accreditation Criteria, ISO/IEC 17025 Application Document Life Sciences – Annex, Asbestos sampling and testing, Issued: April 2025 are realised.

Project Name FINUCANE CRES DSI
Project ID 68409
Date Sampled Jul 23, 2025
Report 1247772-AFC

Eurofins Sample No.	Client Sample ID	Pump ID	Location	Start (time)	End (time)	Start Flow Rate (L/min)	End Flow Rate (L/min)	Result (Fibres/Fields)	Result (Fibres/mL)
25-JI0062870	DM227978	AC148	FINUCANE RESERVE, NORTH BOUNDARY, NW @ 1.5M HIGH	7:01	15:00	2.0	2.0	0/100	< 0.01
25-JI0062871	DM227983	AC018	FINUCANE RESERVE, NORTH BOUNDARY, NE @ 1.5M HIGH	7:02	15:01	2.0	2.0	1/100	< 0.01
25-JI0062872	DM227986	AC100	FINUCANE RESERVE, WEST BOUNDARY @ 1.5M HIGH	7:03	15:02	2.0	2.0	0/100	< 0.01
25-JI0062873	DM228072	AC186	FINUCANE RESERVE, EAST BOUNDARY @ 1.5M HIGH	7:04	15:03	2.0	2.0	0/100	< 0.01
25-JI0062874	DM228337	AC147	FINUCANE RESERVE, SOUTH BOUNDARY, SE @ 1.5M HIGH	7:05	15:04	2.0	2.0	1/100	< 0.01
25-JI0062875	DM228054	AC189	FINUCANE RESERVE, SOUTH BOUNDARY, SW @ 1.5M HIGH	7:06	15:05	2.0	2.0	0/100	< 0.01
25-JI0062876	DM228042	BLANK	BLANK	--	--	--	--	0/100	--

Sample History

Where samples are submitted/analysed over several days, the last date of extraction is reported.

If the date and time of sampling are not provided, the Laboratory will not be responsible for compromised results should testing be performed outside the recommended holding time.

Description	Testing Site	Extracted	Holding Time
Asbestos - LTM-ASB-8010	Sydney	Jul 23, 2025	Indefinite



web: www.eurofins.com.au
email: EnviroSales@eurofinsanz.com

Melbourne 6 Monterey Road Dandenong South VIC 3175 +61 3 8564 5000 NATA# 1261 Site# 1254	Geelong 19/8 Lewalan Street Grovedale VIC 3216 +61 3 8564 5000 NATA# 1261 Site# 25403	Sydney 179 Magowar Road Girraween NSW 2145 +61 2 9900 8400 NATA# 1261 Site# 18217	Canberra Unit 1,2 Dacre Street Mitchell ACT 2911 +61 2 6113 8091 NATA# 1261 Site# 25466	Brisbane 1/21 Smallwood Place Murarrie QLD 4172 +61 7 3902 4600 NATA# 1261 Site# 20794 & 2780	Newcastle 1/2 Frost Drive Mayfield West NSW 2304 +61 2 4968 8448 NATA# 1261 Site# 25079	Perth 46-48 Banksia Road Welshpool WA 6106 +61 8 6253 4444 NATA# 2377 Site# 2370 & 2554	Auckland 35 O'Rorke Road Penrose Auckland 1061 +64 9 526 4551 IANZ# 1327	Auckland (Focus) Unit C1/4 Pacific Rise Mount Wellington Auckland 1061 +64 9 525 0568 IANZ# 1308	Christchurch 43 Detroit Drive Rolleston Christchurch 7675 +64 3 343 5201 IANZ# 1290	Tauranga 1277 Cameron Road Gate Pa Tauranga 3112 +64 9 525 0568 IANZ# 1402
---	--	--	--	--	--	--	--	--	---	--

Company Name: JBS & G Australia (NSW) P/L

Address: Level 8, 179 Elizabeth St
Sydney
NSW 2000

Project Name: FINUCANE CRES DSI

Project ID: 68409

Order No.:

Report #: 1247772

Phone: 02 8245 0300

Fax:

Received: Jul 23, 2025 5:10 PM

Due: Jul 23, 2025

Priority: Same day

Contact Name: Milad Noujaim

Eurofins Analytical Services Manager : Andrew Black

Sample Detail						Asbestos Fibre Count & Concentration
Sydney Laboratory - NATA # 1261 Site # 18217						X
External Laboratory						
No	Sample ID	Sample Date	Sampling Time	Matrix	LAB ID	
1	DM227978	Jul 23, 2025	3:00PM	Air	S25-JI0062870	X
2	DM227983	Jul 23, 2025	3:01PM	Air	S25-JI0062871	X
3	DM227986	Jul 23, 2025	3:02PM	Air	S25-JI0062872	X
4	DM228072	Jul 23, 2025	3:03PM	Air	S25-JI0062873	X
5	DM228337	Jul 23, 2025	3:04PM	Air	S25-JI0062874	X
6	DM228054	Jul 23, 2025	3:05PM	Air	S25-JI0062875	X
7	DM228042	Jul 23, 2025		Air	S25-JI0062876	X
Test Counts						7

Internal Quality Control Review and Glossary General

1. QC data may be available on request.
2. All soil results are reported on a dry basis, unless otherwise stated.
3. Samples were analysed on an 'as received' basis.
4. Information identified on this report in blue indicates data provided by the customer that may impact the results.
5. This report replaces any interim results previously issued.

Holding Times

Please refer to the most recent version of the 'Sample Preservation and Container Guide' for holding times (QS3001).

Units

% w/w:	Percentage weight-for-weight basis, e.g. of asbestos in asbestos-containing finds in soil samples (% w/w)
F/ffd	Airborne fibre filter loading as Fibres (N) per Fields counted (n)
F/mL	Airborne fibre reported concentration as Fibres per millilitre of air drawn over the sampler membrane (C)
g, kg	Mass, e.g. of whole sample (M) or asbestos-containing find within the sample (m)
g/kg	Concentration in grams per kilogram
L, mL	Volume, e.g. of air as measured in AFM (V = r x t)
L/min	Airborne fibre sampling Flowrate as litres per minute of air drawn over the sampler membrane (r)
min	Time (t), e.g. of air sample collection period

Calculations

Airborne Fibre Concentration: $C = \left(\frac{A}{d}\right) \times \left(\frac{N}{n}\right) \times \left(\frac{1}{r}\right) \times \left(\frac{1}{t}\right) = K \times \left(\frac{N}{n}\right) \times \left(\frac{1}{r}\right)$

Asbestos Content (as asbestos): $\% w/w = \frac{(m \times P_A)}{M}$

Weighted Average (of asbestos): $\%_{WA} = \sum \frac{(m \times P_A)_x}{x}$

Terms

%Asbestos	Estimated percentage of asbestos in a given matrix may be derived from knowledge or experience of the material, informed by HSG264 <i>Appendix 2</i> , else assumed to be 15% in accordance with WA DOH <i>Appendix 2</i> (P _A). This estimate is not NATA-accredited.
ACM	Asbestos Containing Materials. Asbestos in a non-asbestos matrix is typically presented in bonded (non friable) condition. For the NEPM and WA DOH, ACM corresponds to material larger than 7 mm x 7 mm.
AF	Asbestos Fines. Asbestos contamination within a soil sample, as defined by WA DOH. Includes loose fibre bundles and small pieces of friable and non-friable material, such as asbestos cement fragments mixed with soil. Considered under the NEPM as equivalent to "non-bonded / friable".
AFM	Airborne Fibre Monitoring, e.g., by the MFM.
Amosite	Amosite Asbestos Detected. Amosite may also refer to Fibrous Grunerite or Brown Asbestos. Identified in accordance with AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly AS 4964-2004.
AS	Australian Standard.
Asbestos Content (as asbestos)	Total %w/w asbestos content in asbestos-containing finds in a soil sample (% w/w).
Chrysotile	Chrysotile Asbestos Detected. Chrysotile may also refer to Fibrous Serpentine or White Asbestos. Identified in accordance with AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly AS 4964-2004.
COC	Chain of Custody.
Crocidolite	Crocidolite Asbestos Detected. Crocidolite may also refer to Fibrous Riebeckite or Blue Asbestos. Identified in accordance with AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly AS 4964-2004.
Dry	Sample is dried by heating before analysis.
DS	Dispersion Staining. The technique required for unequivocal identification of asbestos fibres by PLM.
FA	Fibrous Asbestos. Asbestos-containing material that is wholly or in part friable, including materials with higher asbestos content with a propensity to become friable with handling, and any material previously non-friable and severely degraded. For the NEPM and WA DOH, FA generally corresponds to material larger than 7 mm x 7 mm, although FA may be more difficult to distinguish visibly and may be assessed as AF.
Fibre Count	Total of all fibres (whether asbestos or not) meeting the counting criteria set out in the NOHSC:3003
Fibre ID	Fibre Identification. Unequivocal identification of asbestos fibres according to AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly AS 4964-2004. Includes Chrysotile, Amosite (Grunerite) or Crocidolite asbestos.
Friable	Asbestos-containing materials of any size that may be broken or crumbled by hand pressure. For the NEPM, this includes both AF and FA. It is outside of the laboratory's remit to assess the degree of friability.
HSG248	UK HSE HSG248, <i>Asbestos: The Analysts Guide</i> , 2 nd Edition (2021), ISBN: 9780616667079.
HSG264	UK HSE HSG264, <i>Asbestos: The Survey Guide</i> (2012), ISBN: 9780717665020
ISO (also ISO/IEC)	International Organization for Standardization / International Electrotechnical Commission.
K Factor	Microscope constant (K) as derived from the effective filter area of the given AFM membrane used for collecting the sample (A) and the projected eyepiece graticule area of the specific microscope used for the analysis (a).
LOR	Limit of Reporting.
MFM (also NOHSC:3003)	Membrane Filter Method. As described by the Australian Government National Occupational Health and Safety Commission, <i>Guidance Note on the Membrane Filter Method for Estimating Airborne Asbestos Fibres</i> , 2 nd Edition [NOHSC:3003(2005)].
MMVF	Man-Made Vitreous Fibre - exhibiting isotropic characteristics, including glass fibres, glass wool, rock wool, slag wool, ceramic fibres and "bio-soluble fibres. NOTE: previously known as "synthetic mineral fibre" (SMF).
NEPM (also ASC NEPM)	National Environment Protection (Assessment of Site Contamination) Measure, (2013, as amended).
Organic	Organic Fibres Detected. Organic may refer to Natural or Man-Made Polymeric Fibres. Identified per AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly AS 4964-2004.
PCM	Phase Contrast Microscopy. This is used for fibre counting, according to the MFM.
PLM	Polarised Light Microscopy. It is used for fibre identification and residual analysis according to AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly AS 4964-2004.
Sampling	Unless otherwise stated, Eurofins are not responsible for sampling equipment or the sampling process.
SRA	Sample Receipt Advice.
Residual Analysis	An analytical procedure is used to detect the presence of respirable fibres (particularly asbestos) in a given sample matrix according to AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly Trace Analysis in AS 4964-2004.
UK HSE HSG	United Kingdom, Health and Safety Executive, Health and Safety Guidance, publication.
Inconclusive	Fibrous minerals that are detected but have not been unequivocally identified by PLM with DS according to AS 5370:2024* Sampling and qualitative identification of asbestos in bulk materials (ISO 22262-1:2012, MOD), formerly AS 4964-2004. It may include (but is not limited to) actinolite, anthophyllite, or tremolite asbestos. SEM/TEM is required for definitive identification.
WA DOH	Reference document for the NEPM. Government of Western Australia, <i>Guidelines for the Assessment, Remediation and Management of Asbestos-Contaminated Sites in Western Australia</i> (updated 2021), including Appendix Four: <i>Laboratory analysis</i>
Weighted Average	Combined average %w/w asbestos content of all asbestos-containing finds in the given aliquot or total soil sample (% _{WA}).

Comments

Volume Measurement : David Rowan, JBS & G Australia (NSW) P/L, has been trained by Eurofins and they conducted the sampling in accordance with the National Occupational Health & Safety Commission - Guidance Note on The Membrane Filter Method For Estimating Airborne Asbestos Fibres 2nd Edition [NOHSC:3003(2005)] methodology. Sampling pumps used by JBS & G Australia (NSW) P/L were calibrated by Eurofins Environment Testing and therefore volume measurements contained in this report are traceable back to Eurofins Environment Testing. Eurofins Environment Testing are responsible for all data contained in this report.

Sample Integrity

Custody Seals Intact (if used)	N/A
Attempt to Chill was evident	N/A
Sample correctly preserved	Yes
Appropriate sample containers have been used	Yes
Sample containers for volatile analysis received with minimal headspace	Yes
Samples received within HoldingTime	Yes
Some samples have been subcontracted	No

Asbestos Counter/Identifier:

Geronimo Jr Abrot Senior Analyst-Asbestos

Authorised by:

Sayed Abu Senior Analyst-Asbestos



Glenn Jackson
Managing Director

Final Report – this report replaces any previously issued Report

- Indicates Not Requested

* Indicates NATA accreditation does not cover the performance of this service

Measurement uncertainty of test data is available on request or please [click here](#).

Eurofins shall not be liable for loss, cost, damages or expenses incurred by the client, or any other person or company, resulting from the use of any information or interpretation given in this report. In no case shall Eurofins be liable for consequential damages including, but not limited to, lost profits, damages for failure to meet deadlines and lost production arising from this report. This document shall not be reproduced except in full and relates only to the items tested. Unless indicated otherwise, the tests were performed on the samples as received.