

TEST REPORT

March 27, 2023

Gartner Rose

Level 3, 15 Blue Street NORTH SYDNEY NSW 2060

Your Reference: 5 Knowles Avenue, Matraville NSW 2036

Job Number: 67316

Attention: Taras Cherkasov

Dear Taras,

In accordance with your instructions, Airsafe conducted air monitoring for airborne asbestos fibres at the above site.

The following samples were processed on the dates indicated.

Samples: 5 Filters
Date of Sampling: 24/03/2023
Date of Analysis: 27/03/2023
Date of Preliminary Report Sent: Not Issued

The results are contained in the following pages of this report.

Should you have any queries regarding this report please contact the undersigned.

Regards

AIRSAFE LABORATORIES PTY LTD



Approved Counter and Signatory





PROJECT: 5 Knowles Avenue, Matraville JOB NO: 67316

Sample No	Location/Reference	Time		Total Time	Air Flow Average	Fields	Fibres	Concentration
		On	Off	[min]	[L/min]	rielus	Fibles	(Fibres/mL)
67316-56	Site fencing adjacent site sheds – east of works area	0732	1532	480	1.0	100	0	<0.01
67316-57	Exclusion zone temporary fencing – northeast of works area	0733	1533	480	1.0	100	0	<0.01
67316-58	Site temporary fencing – south of works area	0735	1535	480	1.0	100	0	<0.01
67316-59	Site temporary fencing – west of works area	0736	1536	480	1.0	100	0	<0.01
67316-60	Site temporary fencing – north of works area	0738	1538	480	1.0	100	0	<0.01

Method: Guidance Note on the Membrane Filter Method for Estimating Airborne Asbestos Fibres [NOHSC: 3003

(2005)] and in-house method AS101 – Membrane Filter Method for Estimating Airborne Asbestos Fibres.

Sampling: All samples have been taken by Airsafe personnel in accordance with the sampling plan detailed in method

AS101.

Location of Laboratory Activities: Level 1, 488 Botany Road, Beaconsfield NSW Australia.

Quality Control: A field blank is taken and analysed for each batch of samples.

Environmental Conditions: Background air monitoring during works.

Comment: These calculated concentrations are less than the reporting limit of 0.01 fibres/mL for control and exposure

monitoring as stated in the Guidance Note on the Membrane Filter Method for Estimating Airborne Asbestos

Fibres [NOHSC: 3003 (2005)].

Disclaimer: N/A.

Sampled By: Mitchell Jackson, Licensed Asbestos Assessor [SafeWork NSW Licence No LAA 001599].

Note: The measured results fall within a 95% confidence interval (calculated using a coverage factor of 2) in

accordance with the NOHSC:3003(2005).

The results relate only to the samples tested. The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards.

Airsafe shall not be liable for loss, cost, damages or expenses incurred by the client, or any other person or company, resulting from the use of any information or interpretation given in this report. In no case shall Airsafe be liable for consequential damages including, but not limited to, lost profits, damages for failure to

meet deadlines and lost production arising from this report.

Any other holder of this document is advised that information contained hereon reflects Airsafe's findings at the time of its intervention only and within the limits of Client's instructions, if any. Airsafe's sole responsibility is to its client and this document does not exonerate parties to a transaction from exercising all their rights

and obligations under the transaction documents.

